

UNITED STATES PATENT AND TRADEMARK OFFICE

UNITED STATES DEPARTMENT OF COMMERCE
United States Patent and Trademark Office
Address: COMMISSIONER FOR PATENTS
P.O. Box 1450
Alexandria, Virginia 22313-1450
www.uspto.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
10/708,355	02/26/2004	Hsiang-An Hsieh	12222-US-PA	2354

31561 7590 03/28/2006

JIANQ CHYUN INTELLECTUAL PROPERTY OFFICE
7 FLOOR-1, NO. 100
ROOSEVELT ROAD, SECTION 2
TAIPEI, 100
TAIWAN

EXAMINER

CAMPOS, YAIMA

ART UNIT	PAPER NUMBER
----------	--------------

2185

DATE MAILED: 03/28/2006

Please find below and/or attached an Office communication concerning this application or proceeding.

Office Action Summary	Application No.		Applicant(s)	
	10/708,355		HSIEH, HSIANG-AN	
	Examiner		Art Unit	
	Yaima Campos		2185	

-- The MAILING DATE of this communication appears on the cover sheet with the correspondence address --

Period for Reply

A SHORTENED STATUTORY PERIOD FOR REPLY IS SET TO EXPIRE 3 MONTH(S) OR THIRTY (30) DAYS, WHICHEVER IS LONGER, FROM THE MAILING DATE OF THIS COMMUNICATION.

- Extensions of time may be available under the provisions of 37 CFR 1.136(a). In no event, however, may a reply be timely filed after SIX (6) MONTHS from the mailing date of this communication.
- If NO period for reply is specified above, the maximum statutory period will apply and will expire SIX (6) MONTHS from the mailing date of this communication.
- Failure to reply within the set or extended period for reply will, by statute, cause the application to become ABANDONED (35 U.S.C. § 133). Any reply received by the Office later than three months after the mailing date of this communication, even if timely filed, may reduce any earned patent term adjustment. See 37 CFR 1.704(b).

Status

- 1) ☒ Responsive to communication(s) filed on 26 February 2004.
- 2a) ☐ This action is **FINAL**. 2b) ☒ This action is non-final.
- 3) ☐ Since this application is in condition for allowance except for formal matters, prosecution as to the merits is closed in accordance with the practice under *Ex parte Quayle*, 1935 C.D. 11, 453 O.G. 213.

Disposition of Claims

- 4) ☒ Claim(s) 1-16 is/are pending in the application.
- 4a) Of the above claim(s) _____ is/are withdrawn from consideration.
- 5) ☐ Claim(s) _____ is/are allowed.
- 6) ☒ Claim(s) 1-16 is/are rejected.
- 7) ☐ Claim(s) _____ is/are objected to.
- 8) ☐ Claim(s) _____ are subject to restriction and/or election requirement.

Application Papers

- 9) ☐ The specification is objected to by the Examiner.
- 10) ☒ The drawing(s) filed on 26 February 2004 is/are: a) ☒ accepted or b) ☐ objected to by the Examiner.
Applicant may not request that any objection to the drawing(s) be held in abeyance. See 37 CFR 1.85(a).
Replacement drawing sheet(s) including the correction is required if the drawing(s) is objected to. See 37 CFR 1.121(d).
- 11) ☐ The oath or declaration is objected to by the Examiner. Note the attached Office Action or form PTO-152.

Priority under 35 U.S.C. § 119

- 12) ☒ Acknowledgment is made of a claim for foreign priority under 35 U.S.C. § 119(a)-(d) or (f).
- a) ☐ All b) ☐ Some * c) ☒ None of:
1. ☒ Certified copies of the priority documents have been received.
2. ☐ Certified copies of the priority documents have been received in Application No. _____.
3. ☐ Copies of the certified copies of the priority documents have been received in this National Stage application from the International Bureau (PCT Rule 17.2(a)).

* See the attached detailed Office action for a list of the certified copies not received.

Attachment(s)

- | | |
|------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------|
| 1) <input checked="" type="checkbox"/> Notice of References Cited (PTO-892) | 4) <input type="checkbox"/> Interview Summary (PTO-413)
Paper No(s)/Mail Date. _____ |
| 2) <input type="checkbox"/> Notice of Draftsperson's Patent Drawing Review (PTO-948) | 5) <input type="checkbox"/> Notice of Informal Patent Application (PTO-152) |
| 3) <input type="checkbox"/> Information Disclosure Statement(s) (PTO-1449 or PTO/SB/08)
Paper No(s)/Mail Date _____ | 6) <input type="checkbox"/> Other: _____ |

DETAILED ACTION

1. The instant application having Application No. 10/708,355 has a total of 16 claims pending in the application; there are 4 independent claims and 12 dependent claims, all of which are ready for examination by the examiner.

I. INFORMATION CONCERNING OATH/DECLARATION

Oath/Declaration

2. The applicant's oath/declaration has been reviewed by the examiner and is found to conform to the requirements prescribed in 37 C.F.R. 1.63.

II. STATUS OF CLAIM FOR PRIORITY IN THE APPLICATION

As required by M.P.E.P. 201.14(c), acknowledgement is made of applicant's claim for priority based on applications filed on 12/11/03 (Taiwan 92134971). It is noted, however, that applicant has not filed a certified copy of the application as required by 35 U.S.C. 119(b) and M.P.E.P. 201.14(b).

III. INFORMATION CONCERNING DRAWINGS

Drawings

3. The applicant's drawings submitted are acceptable for examination purposes.

IV. REJECTIONS BASED ON PRIOR ART

Claim Rejections – 35 USC § 102

4. The following is a quotation of the appropriate paragraphs of 35 U.S.C. 102 that form the basis for the rejections under this section made in this Office action:

A person shall be entitled to a patent unless –

(e) the invention was described in (1) an application for patent, published under section 122(b), by another filed in the United States before the invention by the applicant for patent or (2) a patent granted on an application for patent by another filed in the United States before the invention by the applicant for patent, except that an international application filed under the treaty defined in section 351(a) shall have the effects for purposes of this subsection of an application filed in the United States only if the international application designated the United States and was published under Article 21(2) of such treaty in the English language.

5. **Claim 1** is rejected under 35 U.S.C. 102(e) as being anticipated by Chou et al. (US 2005/0055481).

6. As per **claim 1**, Chou discloses “A card reader,” as [“**this invention relates to flash-memory drives/readers**” (Column 1, paragraph 0001, lines 1-2)] “comprising: a silicon storage device connector, electrically coupled to a silicon storage device;” [With respect to this limitation, Chou discloses “**The flash drive/reader of FIGS. 1, 2 can be connected to USB link 128 of the PC in FIG. 3**” (Column 1, paragraph 0011, lines 2-3)] “and a bridge controller, electrically coupled to the silicon storage device connector, wherein when the bridge controller receives a read instruction, the bridge controller prefetches a part of data requested by the read instruction from the silicon storage device in advance, and saves the part of data in the bridge controller” [Chou discloses this limitation as “**prefetching of flash data may be performed by flash-memory controller 30 (Figs. 4,6) or by flash-card controllers 50,54 (Figs. 5,7) writing additional pages of flash data to the RAM buffer. For example, m blocks**

of flash data may be pre-fetched, where m can be a programmable number of pages to pre-fetch ahead of the current page being read” (Column 3, paragraph 0045)].

Claim Rejections - 35 USC § 103

7. The following is a quotation of 35 U.S.C. 103(a) which forms the basis for all obviousness rejections set forth in this Office action:

(a) A patent may not be obtained though the invention is not identically disclosed or described as set forth in section 102 of this title, if the differences between the subject matter sought to be patented and the prior art are such that the subject matter as a whole would have been obvious at the time the invention was made to a person having ordinary skill in the art to which said subject matter pertains. Patentability shall not be negated by the manner in which the invention was made.

8. **Claims 2-16** are rejected under 35 U.S.C. 103(a) as being unpatentable over Wurzburg (US 2005/0097263) in view of Chou (US 2005/0055481).

9. As per **claim 2**, Wurzburg discloses “A bridge controller, embedded in a card reader electrically coupling to a silicon storage device and an external system side,” as [“**the invention comprises a system and method for designing a flash memory card reader to IDE Bridge (IDE-CR Bridge) to create and interface between a flash-memory card-reader and an IDE controller. The IDE controller may be comprised in an embedded system**” (Column 2, paragraph 0019)] “comprising: a microprocessor;” [With respect to this limitation, Wurzburg discloses that “**embedded system 10 includes a microprocessor 12**” (Column 2, paragraph 0020, line 4)] “a silicon storage device interface, accessing said silicon storage device according to instruction of the microprocessor;” [With respect to this limitation, Wurzburg discloses that “**the invention comprises a flash-memory card reader to Integrated Drive Electronics (IDE) Bridge (or interface)**” (Column 1, paragraph 0010, lines 2-3) and explains that “**the internal microprocessor and its program convert the IDE/ATA commands and status/data requests into the formats used by each of the four basic types of**

Art Unit: 2185

Flash Card media” (Column 1, paragraph 0010, lines 13-16)] “a system interface, receiving data transferred from buffers respectively according to instruction of said microprocessor;” [With respect to this limitation, Wurzburg discloses “IDE/ATA interface (IAI)” and explains that “IAI 102 may receive IDE/ATA commands from an IDE controller configured in a host system, (for example IDE controller 22, as illustrated in Fig. 1). The data may be buffered in TRB 104 (*transmit/receive buffer*)” (Column 2, paragraph 0021)] “a transmission buffer, electrically coupled to said silicon storage device interface and said system interface;” [Wurzburg discloses this limitation as “an IDE/ATA interface (IAI) 102 is coupled to a transmit/receive buffer (TRB) 104 and an ATA command/status register emulation buffer (CSRB)” (Column 2, paragraph 0021)].

Wurzburg does not disclose expressly “a cache buffer, overlapping said transmission buffer to couple with said silicon storage device interface and said system interface; wherein, when said microprocessor outputting a read instruction, one of said buffers transferring alternatively to the system interface.”

Chou discloses the concept of having “a cache buffer, overlapping said transmission buffer to couple with said silicon storage device interface and said system interface; wherein, when said microprocessor outputting a read instruction, one of said buffers transferring alternatively to the system interface” as [“**the present invention relates to flash-memory drives/readers**” (Column 1, paragraph 0001) wherein “**prefetching of flash data may be performed by flash-memory controller 30 (Figs. 4,6 or by flash-card controllers 50,54 (Figs. 5,7) writing additional pages of flash data to the RAM buffer**” (Column 3, paragraph 0045) which is equivalent to a transmission buffer. Chou explains that “**additional RAM buffers**

Art Unit: 2185

could be added, or the RAM buffer could be partitioned to allow simultaneous access without arbitration delays of different memory partitions” (Column 4, paragraph 0054) and further teaches an embodiment having “a flash drive with external and internal RAM buffers. Most of the components of the flash drive could be integrated into a single integrated circuit (IC) chip 68” wherein “external RAM buffer 60” is provided “when larger blocks of data are stored, the overflow data is stored in external RAM buffer 60” (Column 3, paragraphs 0037 and 0038) which is equivalent to having a cache buffer to overlap a transmission buffer, as claimed by Applicant. Chou explains that “either internal RAM buffer 34 or external RAM buffer 60 can be accessed through flash-serial buffer bus 40” (Column 3, paragraph 0038, lines 7-9). Applicant should note that if both, the internal and external RAM buffers are holding data, only the buffer holding data requested by a read command will provide this data].

Wurzberg (US 2005/0097263) and Chou (US 2005/0055481) are analogous art because they are from the same field of endeavor of memory card access and control.

At the time of the invention, it would have been obvious to a person of ordinary skill in the art to combine the memory card reader which includes a transmission buffer as taught by Wurzberg and further include an additional cache buffer that overlaps the transmission buffer to receive/output read data alternatively as taught by Chou.

The motivation for doing so would have been because Chou teaches that including and additional cache buffer that overlaps the transmission buffer to receive/output read data alternatively [allows transferring of larger amounts of data as “buffering of the data during the transfer between the flash-memory controller and the serial engine can improve

Art Unit: 2185

throughput” (Column 2, paragraph 0025). Chou also discloses that “additional RAM buffers could be added, or the RAM buffer could be partitioned to allow simultaneous access without arbitration delays of different memory partitions” (Column 4, paragraph 0054)].

Therefore, it would have been obvious to combine Chou (US 2005/0055481) with Wurzburg (US 2005/0097263) for the benefit of creating a memory card reader to obtain the invention as specified in claim 2.

10. As per claim 3, the combination of Wurzburg and Chou discloses “The bridge controller of claim 2,” “an allocation table buffer, electrically coupled to said system interface and said silicon storage device interface for storing a data accessing address mapping table” [See rejection to claim 2 above] and [With respect to this limitation, Wurzburg discloses; “Fig. 2 illustrates a schematic diagram of one embodiment of IDE-CRs” including “an ATA command/status register emulation buffer (CSRB) 106” which equivalent to an allocation table buffer wherein “An address and data bus 160 may couple CSRB 106 and MP 108, enabling data transfer between MP 108, CSRB 106 and a flash media controller (FMC) unit 110 interfacing with the actual flash-memory cards for exchanging commands/status information” (Column 2, paragraph 0021) and also discloses that “Generally, flash-memory card media is very similar to hard disk drives (HDDs) in that flash-memory cards are usually formatted in a Windows file format, such as File Allocation Table (FAT) or NT File System (NTFS)” (Column 1, paragraph 0010)]. Chou also discloses having an address-mapping table as [“Rather than use FIFO buffers, the flash data can be stored out of sequence. A catalog or index can be used to locate the desired pages, or other address

remapping or translation logic may be used” (Column 4, paragraph 0054) which is also equivalent to having allocation table buffer storing an allocation mapping table].

11. As per **claim 4**, the combination of Wurzburg and Chou discloses “The bridge controller of claim 2,” [See rejection to claim 2 above] and claim 4 further requires:

“means for transmitting data transmission operation is alternately and synchronously performed between said cache buffer and said transmission buffer” [(Page 19, paragraph 0042 of *applicant’s specification identifies these means as “cache buffer 120” and “transmission buffer 118”*)] [With respect to this limitation, Chou discloses “internal RAM buffer” and “external RAM buffer” (Column 3, paragraphs 0037-0038) and explains that “Since RAM buffer 34, flash-memory controller 30, and serial engine 32 each have two ports, one for each of buses 38, 40, concurrent accesses can occur” (Column 2, paragraph 0032) as having concurrent/synchronous transmission operations. Applicant should note that if both, the internal and external RAM buffers are holding data, only the buffer holding data requested by a read command will provide this data].

12. As per **claims 5 and 11**, Wurzburg discloses “A method for data transmission of a card reader,” as [“the invention comprises a system and method for designing a flash memory card reader to IDE Bridge (IDE-CR Bridge) to create and interface between a flash-memory card-reader and an IDE controller. The IDE controller may be comprised in an embedded system” (Column 2, paragraph 0019)"] “wherein said card reader comprising a transmission buffer,” [Wurzburg discloses this limitation as “an IDE/ATA interface (IAI) 102 is coupled to a transmit/receive buffer (TRB) 104 and an ATA command/status register emulation buffer (CSRB)” (Column 2, paragraph 0021)] “a system interface” [With respect

Art Unit: 2185

to this limitation, Wurzburg discloses “IDE/ATA interface (IAI)” and explains that “IAI 102 may receive IDE/ATA commands from an IDE controller configured in a host system, (for example IDE controller 22, as illustrated in Fig. 1). The data may be buffered in TRB 104 (*transmit/receive buffer*)” (Column 2, paragraph 0021)] “and a silicon storage device interface,” [With respect to this limitation, Wurzburg discloses that “the invention comprises a flash-memory card reader to Integrated Drive Electronics (IDE) Bridge (or interface)” (Column 1, paragraph 0010, lines 2-3) and explains that “the internal microprocessor and its program convert the IDE/ATA commands and status/data requests into the formats used by each of the four basic types of Flash Card media” (Column 1, paragraph 0010, lines 13-16)] “said method comprising: receiving a first data requested by a read instruction, wherein said first data is received by said transmission buffer;” [Wurzburg discloses this limitation as “FIG. 2 illustrates a schematic diagram of one embodiment of IDE-CR Bridge 26. In this embodiment, an IDE/ATA interface (IAI) 102 is coupled to a transmit and receive buffer (TRB) 104 and an ATA command/status register emulation buffer (CSRB) 106. IAI 102 may receive IDE/ATA commands and data from an IDE controller configured in a host system, (for example IDE controller 22, as illustrated FIG. 1). The data may be buffered in TRB 104” (Column 2, paragraph 0021)].

Wurzburg does not disclose having “a cache buffer,” and “storing a second data predetermined by said read instruction into either said cache buffer or said transmission buffer when either buffer is approaching full status; and outputting sequentially said data stored in said transmission buffer and said cache buffer.”

Chou discloses having “a cache buffer,” and “storing a second data predetermined by said read instruction into either said cache buffer or said transmission buffer when either buffer is approaching full status; and outputting sequentially said data stored in said transmission buffer and said cache buffer.” [With respect to these limitations, Chou discloses [“the present invention relates to flash-memory drives/readers” (Column 1, paragraph 0001) wherein “prefetching of flash data may be performed by flash-memory controller 30 (Figs. 4,6 or by flash-card controllers 50,54 (Figs. 5,7) writing additional pages of flash data to the RAM buffer” (Column 3, paragraph 0045) which is equivalent to a transmission buffer or a cache buffer. Chou explains that “additional RAM buffers could be added, or the RAM buffer could be partitioned to allow simultaneous access without arbitration delays of different memory partitions” (Column 4, paragraph 0054) and further teaches an embodiment having “a flash drive with external and internal RAM buffers. Most of the components of the flash drive could be integrated into a single integrated circuit (IC) chip 68” wherein “external RAM buffer 60” is provided “when larger blocks of data are stored, the overflow data is stored in external RAM buffer 60” (Column 3, paragraphs 0037 and 0038) which is equivalent to having a second buffer in addition to a first buffer, as claimed by Applicant. Chou explains that “either internal RAM buffer 34 or external RAM buffer 60 can be accessed through flash-serial buffer bus 40” (Column 3, paragraph 0038, lines 7-9). Applicant should note that if both, the internal and external RAM buffers are holding data, only the buffer holding data requested by a read command will provide this data. Chou further specifies that “Once one or more blocks of flash data have been written into RAM buffer 34 by flash-memory controller 30, serial engine 32 can read the flash data and

serially transmit the flash data over USB link 18, uploading the data to a PC or other device” (Column 2, paragraph 0027)].

Wurzberg (US 2005/0097263) and Chou (US 2005/0055481) are analogous art because they are from the same field of endeavor of memory card access and control.

At the time of the invention, it would have been obvious to a person of ordinary skill in the art to combine the memory card reader which includes a transmission/first buffer as taught by Wurzberg and further include an additional cache/second buffer to store read data when the either buffer is approaching full status as taught by Chou.

The motivation for doing so would have been because Chou teaches that including and additional buffer to store read data when a first buffer is approaching full status **[allows transferring of larger amounts of data as “buffering of the data during the transfer between the flash-memory controller and the serial engine can improve throughput” (Column 2, paragraph 0025). Chou also discloses that “additional RAM buffers could be added, or the RAM buffer could be partitioned to allow simultaneous access without arbitration delays of different memory partitions” (Column 4, paragraph 0054)].**

Therefore, it would have been obvious to combine Chou (US 2005/0055481) with Wurzberg (US 2005/0097263) for the benefit of creating a memory card reader to obtain the invention as specified in claims 5 and 11.

13. As per **claims 6 and 12**, the combination of Wurzberg and Chou discloses “The method as cited in claims 5 and 11,” **[See rejection to claims 5 and 11 above]** “said method further comprising a step for comparing said data stored in said buffers following said step of storing said second data, wherein said comparison step determining the first position of said second data

Art Unit: 2185

following the last position of said first data” [Chou discloses this concept as it is taught that “the flash controller can then pre-fetch another m pages from the new current location. The write pointer is set to the end of the page being read, or to the end of the block of pre-fetched data includes the page being read by the serial engine” (Column 3, paragraph 0047). Applicant should note that if a pointer is placed at the end of a first pre-fetched block of data, the position for any new/second data to be prefetched will follow the last position of the first data. Chou also explains; “hardware comparators of other logic can be used to detect full and empty conditions. The CPU can write the starting and ending locations, allowing CPU to adjust memory allocations for read and write buffers” (Column 3, paragraph 0044)].

14. As per claims 7 and 13, the combination of Wurzburg and Chou discloses “The method as cited in claims 5 and 11,” [See rejection to claims 5 and 11 above] “further comprising: removing said data from said transmission buffer and said cache buffer after outputting said data” [Chou discloses this limitation as “when the serial engine causes the read pointer to move past old pre-fetched data, the old data is discarded” (Column 4, paragraph 0049)].

15. As per claims 8 and 14, the combination of Wurzburg and Chou discloses “The method as cited in claims 5 and 11,” [See rejection to claims 5 and 11 above] “wherein said method is alternately and synchronously performed to transmit data” [With respect to this limitation, Chou discloses that “Since RAM buffer 34, flash-memory controller 30, and serial engine 32 each have two ports, one for each of buses 38, 40, concurrent accesses can occur” (Column 2, paragraph 0032) as having concurrent/synchronous transmission operations.

Applicant should note that if both, the internal and external RAM buffers are holding data, only the buffer holding data requested by a read command will provide this data].

16. As per claims 9 and 15, the combination of Wurzburg and Chou discloses “The method as recited in claims 5 and 11” [See rejection to claims 5 and 11 above] “said card reader further comprising an allocation table buffer, and said method writing a data accessing address mapping table into said allocation table buffer;” [With respect to this limitation, Wurzburg discloses; “Fig. 2 illustrates a schematic diagram of one embodiment of IDE-CRs” including “an ATA command/status register emulation buffer (CSRB) 106” wherein “An address and data bus 160 may couple CSRB 106 and MP 108, enabling data transfer between MP 108, CSRB 106 and a flash media controller (FMC) unit 110 interfacing with the actual flash-memory cards for exchanging commands/status information” (Column 2, paragraph 0021) and also discloses that “Generally, flash-memory card media is very similar to hard disk drives (HDDs) in that flash-memory cards are usually formatted in a Windows file format, such as File Allocation Table (FAT) or NT File System (NTFS)” (Column 1, paragraph 0010)]. Chou also discloses having an address-mapping table as [“Rather than use FIFO buffers, the flash data can be stored out of sequence. A catalog or index can be used to locate the desired pages, or other address remapping or translation logic may be used” (Column 4, paragraph 0054)] “updating content of said data accessing address mapping table with a written data according to a write instruction; writing said written data into said silicon storage device through said silicon storage device interface from said cache buffer according to said content updated of said data accessing address mapping table; and writing said data accessing address mapping table into said silicon storage device after

Art Unit: 2185

completion of writing operation into said silicon storage device” as [With respect to this limitation Wurzburg discloses that “transfer of commands (translated by MP (*microprocessor*)108) between MP 108 and flash-memory card controllers may take place through control” wherein “Outgoing commands/status/data generated by the flash-memory card controller may be translated into hard disk commands/status/data usable by the hard disk controller (310), and those hard disk commands/status/data may be provided to the hard disk controller (312). The outgoing commands/status may be generated in response to the incoming commands/status and may comprise read and/or write commands” (Column 3, paragraphs 0022 and 0023) as having read/write commands and translation/decoding means for microprocessor instructions. Chou also explains and embodiment wherein a FIFO buffer and a pointer are used for address mapping, having functionality equivalent to Applicant’s claimed invention wherein “FIGS. 9A, B show flash-data buffers in the RAM buffer. FIFO buffers can be used for read and write data. FIG. 9A shows write buffer 160 that stores data to be written into a flash memory. Starting and ending locations of write buffer 160 in the RAM buffer can be indicated by start location ST_WB and end location END_WB. The current location for the serial engine to write the next word or block of flash data is pointed to by pointer W_WB_PTR, while the next location for the flash controller to read from is indicated by R_WB_PTR. These pointers are advanced when data is read or written. The pointers can wrap around at the end of write buffer 160. When the write pointer reaches the read pointer the buffer is full and can accept no more data. When the read pointer reaches the write pointer the buffer is empty. Active write-buffer data 162 is the valid data between the two pointers” (Column 3,

Art Unit: 2185

paragraph 0042); further explains that “blocks or pages of flash memory can be stored in a variety of arrangements” (Column 3, paragraph 0043) wherein “Rather than use FIFO buffers, the flash data can be stored out of sequence. A catalog or index can be used to locate the desired pages, or other address remapping or translation logic may be used” (Column 4, paragraph 0054) as specifying that addressing/mapping data may be stored in a table/index form in a buffer instead of using pointers to read/write data to buffers].

17. As per claims 10 and 16, the combination of Wurzburg and Chou discloses “The method as cited in claims 9 and 15,” [See rejection to claims 9 and 15 above] “wherein said step of writing said written data into said silicon storage device through said silicon storage device interface from said cache buffer processing simultaneously with decoding data of said microprocessor” [With respect to this limitation, Wurzburg discloses “transfer of commands (translated by MP (*microprocessor*)108) between MP 108 and flash-memory card controllers may take place through control” wherein “Outgoing commands/status/data generated by the flash-memory card controller may be translated into hard disk commands/status/data usable by the hard disk controller (310), and those hard disk commands/status/data may be provided to the hard disk controller (312). The outgoing commands/status may be generated in response to the incoming commands/status and may comprise read and/or write commands” (Column 3, paragraphs 0022 and 0023) as having read/write commands and translation/decoding means for microprocessor instructions].

Art Unit: 2185

V. RELEVANT ART CITED BY THE EXAMINER

18. The following prior art made of record and not relied upon is cited to establish the level of skill in the applicant's art and those arts considered reasonably pertinent to applicant's disclosure. See **MPEP 707.05(c)**.

19. The following references teach memory card systems having multiple interfaces.

U.S. PATENT NUMBER

US 6,385,677

US 2003/0212848

US 6,712,277

20. The following reference teaches having data caches which prefetch data words associated with a particular addressing mode.

U.S. PATENT NUMBER

US 5,829,028

21. The following reference teaches access operation for a large block flash memory.

U.S. PATENT NUMBER

US 2005/0055493

22. The following reference teaches a removable medium data storage apparatus which include a read circuit for reading data, a buffer for temporarily storing read data, and a MPU wherein data can be prefetched according to the read pattern each time the medium is loaded.

US 5,829,017

VI. CLOSING COMMENTS

Conclusion

a. STATUS OF CLAIMS IN THE APPLICATION

23. The following is a summary of the treatment and status of all claims in the application as recommended by M.P.E.P. 707.07(i):

a(1) CLAIMS REJECTED IN THE APPLICATION

24. Per the instant office action, claims 1-16 have received a first action on the merits and are subject of a first action non-final.

b. DIRECTION OF FUTURE CORRESPONDENCES

25. Any inquiry concerning this communication or earlier communications from the examiner should be directed to Yaima Campos whose telephone number is (571) 272-1232. The examiner can normally be reached on Monday to Friday 8:30 AM to 5:00 PM.

IMPORTANT NOTE

26. If attempts to reach the above noted Examiner by telephone are unsuccessful, the Examiner's supervisor, Mr. Donald Sparks, can be reached at the following telephone number:
Area Code (571) 272-4201.


The fax phone number for the organization where this application or proceeding is assigned is 571-273-8300. Information regarding the status of an application may be obtained from the Patent Application Information Retrieval (PAIR) system. Status information for published applications may be obtained from either Private PAIR or Public PAIR. Status

Art Unit: 2185

information for unpublished applications is available through Private PAIR only. For more information about the PAIR system, see <http://pair-direct.uspto.gov>. Should you have questions on access to the Private PAIR system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free).

March 16, 2006

Yaima Campos
Examiner
Art Unit 2185

A handwritten signature in black ink, appearing to read "Donald Sparks", written over a printed name.

DONALD SPARKS
SUPERVISORY PATENT EXAMINER